

## TYPES OF **MaxxLuxx**® PRODUCTS



- FRONT ILLUMINATED (FL)**
- strength of material 23/33 mm
  - back side and sides painted
  - front illuminated
  - stroke width min. 12 mm



- FRONT AND BACK ILLUMINATED COMBINED (FL-R)**
- material strength 23/33 mm
  - sides painted
  - front and back illuminated
  - stroke width min. 12 mm



- FRONT ILLUMINATED WITH PARTIALLY ILLUMINATION TO THE SIDE (FL-T)**
- strength of material 23/33 mm
  - Back side and min 10 mm of the rear side painted
  - Front side illuminated, partially to the side illuminated
  - stroke width min. 12 mm



- OUTLINE ILLUMINATED (KL)**
- strength of material 10/20/30 mm
  - back side and the sides painted
  - front side (standard) opaque vinyl with smaller outline as the acrylic face
  - front side (optional) painted, acrylic glass light proof, stainless steel, aluminum, brass
  - outline illuminated onto the front side
  - stroke width min. 14 mm



- BACK ILLUMINATED (RL)**
- strength of material 10/20/30 mm
  - front side and sides painted
  - front side (optional) stainless steel, aluminum, brass
  - back side illuminated
  - stroke width min. 12 mm



- BACK ILLUMINATED WITH ILLUMINATED SIDES (RL/S)**
- strength of material 10/20/30 mm
  - front side (standard) opaque vinyl
  - front side (optional) painted, acrylic glass light proof, stainless steel, brass
  - sides and back side illuminated
  - stroke width min. 12 mm



- SIDE ILLUMINATED (SL)**
- strength of material 10/20/30 mm
  - back side (standard) opaque vinyl
  - backside (optional) painted
  - front side (standard) opaque vinyl
  - front side (optional) painted, opaque acrylic glass, stainless steel, aluminum, brass
  - sides illuminated
  - stroke width min. 12 mm



- SIDE ILLUMINATED WITH PARTIALLY PAINTED SIDE 1 (SL/T1)**
- strength of material 10/20/30 mm
  - front side and obverse side (standard) partially painted
  - front side (optional) stainless steel, aluminum, brass
  - back side (standard) opaque vinyl film
  - back side (optional) painted
  - rear side illuminated
  - stroke width min 12 mm



- SIDE ILLUMINATED WITH PARTIALLY LACQUERED SIDE 2 (SL/T2)**
- strength of material 10/20/30 mm
  - front side (standard) film light proof and color film
  - front side optional painted, acrylic glass light proof, stainless steel, aluminum, brass
  - rear part of the side and backside painted
  - obverse side illuminated
  - stroke width min. 12 mm



- BACK ILLUMINATED MADE FROM PVC INTEGRAL FOAM (RL-ECO)**
- strength of material 13/24/30/48 mm
  - frontside and sides painted
  - sides are not primed and can be porose
  - back side illuminated only for matt surfaces
  - stroke width min. 12 mm

# MaxxLuxx®

## ADVERTISEMENT WITH LED



### MaxxLuxx® – the original

Since more than 10 years we have been producing high quality advertisement, architect and interior lightnings as well as light objects with LED illumination. The complete production process inclusively LED assembly is realized in Dresden. In addition to the specially developed MaxxLuxx® products we are producing **channel letters** made in profile 3/4/5/8 as well as unenlightened letters made from plastic material or metal. We are working only with resellers. German and international top brands have confidence in the quality of our products. Long standing experience in processing of LED and continuous development and improvement meet the high quality demands of MaxxLuxx® products. Express quotations, quick delivery and high flexibility are our strong points.

MaxxLuxx® - Your local sales partner

**BR BLUE RHINE**  
INDUSTRIES L.L.C.  
*The LED Sign Specialists!*

MaxxLuxx® products you can get by

### VGS MARKETINGSERVICE GMBH

BÄRENSTEINER STR. 23/25  
D - 01277 DRESDEN  
FON +49 / (0)351 / 2 58 56 64-0  
FAX +49 / (0)351 / 2 52 28 83  
vgs-dd@t-online.de  
www.vgs-leuchttechnik.de

FIRST CHOICE  
THE ORIGINAL  
BEST QUALITY



# MaxxLuxx®

## ADVERTISEMENT WITH LED